

IGP10, IGP20 Intelligent Gauge Pressure Transmitters
IAP10 Intelligent Absolute Pressure Transmitter

- IGP10 for compact light weight and direct-to-process mounting (bracket optionally available)
- IGP20, bracket mounted, for lower ranges, more material options, and vacuum service
- Field-proven silicon strain gauge technology
- Corrosion-resistant epoxy finish
- Accuracy to $\pm 0.07\%$ of span
- Ambient temperature effects to $\pm 0.2\%$ URL per 55°C (100°F) change
- Intelligent FOXCOM & HART / 4 to 20 mA version or economical 4 to 20 mA version
- LCD Indicator / Pushbutton Configurator to set zero, span, display units, etc. Optional on Digital / 4 to 20 mA version, Standard on 4 to 20 mA version



sales@5gplc.com

+86 13306036024

These Intelligent, two-wire transmitters provide precise, reliable, measurement of gauge or absolute pressure, and transmit a 4 to 20 mA output signal with a superimposed HART/ FOXCOM digital signal for remote configuration and monitoring.

IGP10 Span, Range and Overrange Limits
IAP10 Span, Range and Overrange Limits

Span Limits Code	Span Limits			Range Limits			Maximum Overrange		
	kPa	psi	bar (kg/cm ²)	kPa	psi	bar (kg/cm ²)	kPa	psi	bar (kg/cm ²)
C	7 & 210	1 & 30	0.07 & 2.1	0 & 210	0 & 30	0 & 2.1	310	45	3.15
D	70 & 2100	10 & 300	0.7 & 21	0 & 2100	0 & 300	0 & 21	3100	450	31.5
E	700 & 21000	100 & 3000	7 & 210	0 & 21000	0 & 3000	0 & 210	31000	4500	315

IGP20 Span, Range and Overrange Limits

Span Limits Code	Span Limits			Range Limits			Maximum Overrange		
	kPa	psi	bar (kg/cm ²)	kPa	psi	bar (kg/cm ²)	kPa	psi	bar (kg/cm ²)
B	0.87 & 50	0.125 & 7	0.0087 & 0.5	-50 & 50	-7 & 7	-0.5 & 0.5	25000	3625	250
C	7 & 210	1 & 30	0.07 & 2.1	-100 & 210	-14.7 & 30	-1 & 2.1	25000	3625	250
D	70 & 2100	10 & 300	0.7 & 21	-100 & 2100	-14.7 & 300	-1 & 21	25000	3625	250
E	700 & 21000	100 & 3000	7 & 210	-100 & 21000	-14.7 & 3000	-1 & 210	25000	3625	250

Temperature Limits

	Fill fluid Fluorinert	Fill fluid Silicone
Ambient:	-29 to 85 °C (-20 to 185 °F)	-40 to 85 °C (-40 to 185 °F)
Sensor:	-29 to 121 °C (-20 to 250 °F)	-46 to 121 °C (-50 to 250 °F)

Accuracy (Includes Linearity, Hysteresis, and Repeatability)

Electronics Version	Configured Output Signal	Accuracy in % of Calib. Span
-D & -T	Digital 4 to 20 mA	± 0.07 ± 0.1
	4 to 20 mA	± 0.2

Ambient Temperature Effect

Total effect for a 55 °C (100 °F) change within Normal Operating Conditions limit is:

- Electronics -D, -T: ± 0.2 % of URL
- Electronics -I: ± (0.2 % of URL + 0.1 % of span)

For complete specifications, refer to Product Specification Sheet PSS 2A-1C13 B

Model Codes IGP10

<p>Intelligent, Process Connected Gauge Pressure Transmitter Electrical Versions and Output Signal</p>			IGP10
Intelligent; Digital FoxCom and/or 4 to 20 mA dc, Configurable			-D
Intelligent; Digital HART and 4 to 20 mA			-T
4 to 20 mA Analog Output, Explosionproof and Intrinsically Safe			-I
<p>Structure Code - Process Connection, Sensor, and Fill Fluid</p>			
Process Connection Mat'l	Sensor	Fill Fluid	
316L ss	Co-Ni-Cr	Silicone	20
316L ss	Co-Ni-Cr	Fluorinert	21
316L ss	316L ss	Silicone	22
316L ss	316L ss	Fluorinert	23
<p>Span Limits - Absolute or Gauge Pressure Units, as Applicable</p>			
MPa	psi	bar or kg/cm ²	
0.007 and 0.21	1 and 30	0.07 and 2.1	C
0.07 and 2.1	10 and 300	0.7 and 21	D
0.7 and 21	100 and 3000	7 and 210	E
<p>Conduit Connection</p>			
1/2 NPT Conduit Connection, Both Sides			1
PG 13.5 Conduit Connection, Both Sides (available only with Electrical Safety Codes E & N)			2
<p>Electrical Safety (See Electrical Safety Specifications Section)</p>			
CENELEC Certified Intrinsically Safe, ia			E
CSA Certified			N
EUROPEAN Ex, N, IIC, Nonsparking			C
FM Approved			F
SAA Certified, EEx, d, IIC			A
<p>Options</p>			
<p>Mounting Bracket Set</p>			
Painted Steel Bracket with Plated Steel Bolts			M1
Stainless Steel Bracket with Stainless Steel Bolts			M2
<p>Digital Indicator with Pushbuttons (standard equipment on IGP10-I)</p>			
Digital Indicator, Pushbuttons, and Window Cover (for Electr Version D & T only)			-I.1
<p>Vent Screw and Block & Bleed Valve</p>			
Vent Screw in Process Connection for IGP10/IAP10; or in High Side Process Cover for IGP20			V1
Block and Bleed Valve, Carbon Steel			V2
Block and Bleed Valve, 316 ss			V3
Block and Bleed Valve, 316 ss Body w/Monel Trim (NACE Approved)			V4
<p>Conduit Thread Adapters</p>			
Hawke-Type 1/2 NPT Cable Gland for use with Conduit Connection Code "1"			A1
Plastic PG 13.5 Connector for use with Conduit Connection Code "2" (available only with Electrical Safety Codes E & N)			A2
M20 Connector for use with Conduit Connection Code "1"			A3
<p>Electronics Housing Features</p>			
External Zero Adjustment			Z1
Custody Transfer Lock and Seal			Z2
External Zero Adjustment and Custody Transfer Lock and Seal			Z3
<p>Factory Configuration</p>			
Digital Output (4 to 20 mA Default if not selected)			C1
Full Factory Configuration (Requires Configuration Form to be filled out)			C2
<p>Miscellaneous Optional Selections</p>			
G 1/2 B Manometer Process Connection (Not Available with Option *-V1*)			G
R 1/2 Process Connection (1/2 NPT to R 1/2 Adapter)			R
Five Year Warranty			W
Supplemental Customer Tag (Stainless Steel Tag wired onto Transmitter)			T

Model Codes IGP20

Intelligent Bracket-Mounted Gauge Pressure Transmitter		IGP20
Electronics Versions and Output Signal		
Digital, FOXCOM, or 4 to 20 mA dc, Software Selectable		D
Digital, HART/4 to 20 mA		T
4 to 20 mA		I
Structure Code - Process Cover, Sensor Material, and Sensor Fill Fluid		
Hi-Side Cover - Sensor Material - Fill Fluid		
Steel - Co-Ni-Cr - Silicone		11
Steel - Co-Ni-Cr - Fluorinert		12
Steel - 316L ss - Silicone		13
Steel - 316L ss - Fluorinert		16
Steel - Hastelloy C - Silicone		17
Steel - Hastelloy C - Fluorinert		20
316 ss - Co-Ni-Cr - Silicone	Value Package	21
316 ss - Co-Ni-Cr - Fluorinert		22
316 ss - 316L ss - Silicone		23
316 ss - 316L ss - Fluorinert		26
316 ss - Hastelloy C - Silicone		27
316 ss - Hastelloy C - Fluorinert		46
Hastelloy C - Hastelloy C - Silicone		47
Hastelloy C - Hastelloy C - Fluorinert		
Span Limits (Differential Pressure Units)		
kPa - psi - mbar - inH ₂ O - mmHg		
0.87 and 50 - 0.125 and 7 - 8.7 and 500 - 3.5 and 200 - 6.5 and 375		B
MPa - psi - bar or kg/cm ² - inH ₂ O - mmHg		
0.007 and 0.21 - 1 and 30 - 0.07 and 2.1 - 28 and 840 - 52 and 1550		C
0.07 and 2.1 - 10 and 300 - 0.7 and 21		D
0.7 and 21 - 100 and 3000 - 7 and 210		E
Process Connector Type (Material Same as Process Cover Material)		
None, Cover tapped for 1/4 NPT		0
1/4 NPT		1
1/2 NPT		2
Rc 1/4		3
Rc 1/2		4
1/2 Schedule 80 Welding Neck		6
Conduit Connection		
1/2 NPT Conduit Connection, Both Sides		1
PG 13.5 Conduit Connection, Both Sides (available only with Electrical Safety Codes E & N)		2
Electrical Safety (See Electrical Safety Specifications Section for Description)		
CENELEC Certified Intrinsically Safe, ia		E
CENELEC Certified Flameproof, d		D
CSA Certified, ia, d, and n		C
EUROPEAN Ex N, IIC, Nonsparking		N
FM Approved, ia, d, and n		F
SAA Certified, EEx, d, IIC		A
Options		
Mounting Bracket Set		
Painted Steel Bracket with Plated Steel Bolts		M1
Stainless Steel Bracket with Stainless Steel Bolts		M2
Indicator with Internal Pushbuttons (Standard equipment on Electr. Version I)		
Digital Indicator, Pushbuttons, and Window Cover, for Electr. Version D & T only		L1
DIN 19213 Construction, used with Process Connector Code 0 and 316 ss Covers Only(b)		
Single Ended Process Cover with M10, B7 Steel Bolting		D1
Double Ended Process Cover with M10, B7 Steel Bolting (Blind Kidney Flange on Back)(c)(d)		D2
Single Ended Process Cover with 7/16 in, B7 Steel Bolting		D3
Double Ended Process Cover with 7/16 in, B7 Steel Bolting (Blind Kidney Flange on Back)(c)(d)		D4
Cleaning and Preparation		
Unit Degreased - (Not for Oxygen/Chlorine) (Available only with Structure Codes having Silicone)		X1
Cleaned and Prepared for Oxygen Service (Available only with Structure Codes having Fluorinert and not available with carbon steel process covers)		X2
Cleaned and Prepared for Chlorine Service (Available only with Structure Codes having Fluorinert and not available with carbon steel process covers) (Includes 17-4 ss bolts; do not specify option B2)		X3
Bolting for Process Covers and Process Connectors		
316 ss Bolts and Nuts (Maximum upper range limit pressure 150 bar or 2175 psi)		B1
17-4 ss Bolts and Nuts		B2

(continued on next page)

HighFive PLC
 sales@5gplc.com
 +86 13306036024

Model Codes IGP20 (continued)

Conduit Thread Adapter	
Hawke-Type 1/2 NPT Cable Gland (for use with 1/2 NPT Conduit Connection Code 1)	A1
Plastic PG 13.5 Connector (for use with PG 13.5 Conduit Connection Code 2) (available only with Electrical Safety Codes E & N)	A2
M20 Connector (for use with 1/2 NPT Conduit Connection Code 1)	A3
Electronics Housing Features	
Membrane Keypad	Z1
Optional Keypad Lock and Seal	Z2
External Zero Adjustment and Custody Transfer Lock and Seal	Z3
Factory Configuration	
Digital Output (4 to 20 mA Default if not selected) (Electr. Version D only)	C1
Full Factory Configuration (Requires Configuration Form)	C2
Mounting Connectors	
Stainless Steel, Connecting 6 mm Tubing to 1/4" NPT Process Connector	E1
Stainless Steel, Connecting 6 mm Tubing to 1/2" NPT Process Connector	E2
316 ss, Connecting 6 mm Tubing to 1/4" NPT Process Connector	E3
316 ss, Connecting 12 mm Tubing to 1/2" NPT Process Connector	E4
Miscellaneous Optional Selections	
Vent Screw In Side of Process Cover	V
Five Year Warranty	W
Supplemental Customer Tag	T

(a) Refer to PSS 2A-129 E for option descriptions, and for additional optional features and accessories not listed in Model Code.

(b) See Functional Specifications section for pressure deratings when certain DIN 19213 versions are specified.

(c) Temperature limits derated to 0 and 60°C (32 and 140°F).

(d) Mounting Set option is not available.

Model Codes IAP10

Intelligent Direct Connected Absolute Pressure Transmitter		IAF 0
Electronics Versions and Output Signal		
Digital FOXCOM or 4 to 20 mA dc, Software Selectable		-D
Digital HART and 4 to 20 mA		-T
4 to 20 mA Analog Output		-I
Structure Code - Process Connection, Sensor, and Fill Fluid		
Process Connection Mat'l	Sens or Fill Fluid	
316L ss	Co-Ni-Cr Silicone . . . Val. Pkg.	20
316L ss	Co-Ni-Cr Fluorinert	21
316L ss	316L ss Silicone	22
316L ss	316L ss Fluorinert	23
Span Limits - Absolute or Gauge Pressure Units, as Applicable		
MPa	psi	bar or kg/cm ²
0.007 and 0.21	1 and 30	0.07 and 2.1
0.07 and 2.1	10 and 300	0.7 and 21
0.7 and 21	100 and 3000	7 and 210
		C
		D
		E
Conduit Connection		
1/2 NPT Conduit Connection, Both Sides		1
PG 13.5 Conduit Connection, Both Sides (available only with Electrical Safety Codes E & N)		2
Electrical Safety (See Electrical Safety Specifications Section)		
CENELEC Certified Intrinsically Safe, ia		E
CSA Certified		C
EUROPEAN Ex, N, IIC, Nonsparking		N
FM Approved		F
SAE Certified, EEx, d, IIC		A
Options		
Mounting Bracket Set		
Painted Steel Bracket with Plated Steel Bolts		M1
Stainless Steel Bracket with 316 ss Bolts		M2
Indicator with Pushbuttons (standard equipment on IGP10-4)		
Digital Indicator, Pushbuttons, and Window Cover (for Electr Version D & T only)		-L1
Vent Screw and Block & Bleed Valve		
Vent Screw in Process Connection for IGP10/IAP 10; or in High Side Process Cover for IGP20		V1
Block and Bleed Valve, Carbon Steel		V2
Block and Bleed Valve, 316 ss		V3
Block and Bleed Valve, 316 ss Body w/Monel Trim (NACE Approved)		V4
Conduit Thread Adapters		
Hawke-Type 1/2 NPT Cable Gland for use with Conduit Connection Code "1"		A1
Plastic PG 13.5 Connector for use with Conduit Connection Code "2" (available only with Electrical Safety Codes E & N)		A2
M20 Connector for use with Conduit Connection Code "1"		A3
Electronics Housing Features		
External Zero Adjustment		Z1
Custody Transfer Lock and Seal		Z2
External Zero Adjustment and Custody Transfer Lock and Seal		Z3
Factory Configuration		
Digital Output (4 to 20 mA Default if not selected)		C1
Full Factory Configuration (Requires Configuration Form to be filled out)		C2
Miscellaneous Optional Selections		
G 1/2 B Manometer Process Connection (Not Available with Option "-V1")		G
R 1/2 Process Connection (1/2 NPT to R 1/2 Adapter)		R
Five Year Warranty		W
Supplemental Customer Tag (Stainless Steel Tag wired onto Transmitter)		T

HighFive PLC
 sales@5gplc.com
 +86 13306036024